

KEY STAR 500 ELECTROMECHANICAL GEAR MOTOR



FEATURES

- -Opening mechanical stop to control gate movement
- -Robust with movement fluidity
- -Protection of parts from the elements
- -Easy mechanical release

ACCESSORIES

- -Horizontal Electrolock
- -Mechanical Closing Stop
- -Front/Rear Welded **Brackets**
- -Control unit for two motors
- -Warning Board

SPECIFICATIONS	STAR	500
	01/111	

CONTROL BOARD 14 AB 2 **MAXIMUM LENGTH** 4m **POWER SUPPLY** 230v **MOTOR VOLTAGE** 24v **POWER INPUT** 120w **LOCKING** Mechanical

RELEASE Manual Release FREQUENCY OF USE Low to Medium OPENING TIME AT 90° 25 seconds

MAXIMUM ANGLE 100° PROTECTION STANDARD **IP44**

DIMENSIONS 995mm (L) x 108mm (P) x 110mm (H)

WORKING TEMPERATURE -20°C to +55°C

LEAVES MAXIMUM WEIGHT

500kg

Gate Opening Systems Pty Ltd

Factory 2 / II Leader Street Campbellfield VIC 3061 Ph: 03 9305 3034

Website: www.gateopeningsystems.com.au Email: gates@gateopeningsystems.com.au

> Cantilever

> Slide

> Swing

> Boom